


TELEHANDLER ATTACHMENTS GUIDE


HOPPER | GRAPPLE | TELE-TACH | BALE SPEARS | WORK PLATFORM | HOOK
TRUSS JIBS | BUCKET | SPREADER BAR


KOREX ATTACHMENTS AND IMPLEMENTS HELP YOU GET MORE DONE IN LESS TIME


KOREX offers products for mother handlers including platforms, truss jobs, swivel parts, hooks and many other pedals.

Trash Hopper					
	Model	KDTH 455	KDTH 457	KDTH 458	KDTH 459
	Size (HxDxW)	4'x5'x5'	4'x5'x7'	4'x5'x8'	4'x5'x9'
	Capacity	3.5 yd ³	5.0 yd ³	5.7 yd ³	6.5 yd ³
	Weight	730 lbs	920 lbs	1,020 lbs	1,135 lbs


Concrete Hoppers					
	Model	KDCH-M75	KDCH-M125	KDCH-H75	KDCH-H125
	Chute Operation	Manual Door	Manual Door	Hydraulic Door	Hydraulic Door
	Capacity	$\frac{3}{4}$ yard	1 $\frac{1}{4}$ yard	$\frac{3}{4}$ yard	1 $\frac{1}{4}$ yard
	Weight	570 lbs	680 lbs	580 lbs	690 lbs
	Concrete Hopper Width	52"	52"	52"	52"
	Concrete Hopper Length(Overall)	53"	53"	53"	53"
	Concrete Hopper Height	55"	55"	55"	55"
	Approx weight of concrete hopper	530 lb	530 lb	530 lb	530 lb


Bale Grapple							
	Model	KDBGT-72	KDBGT-72 RG	KDBGT-84	KDBGT-84 RG	KDBGT-96	KDBGT-96 RG
	Telehandler Mount	72" Bale Grapple Bolt-on Edge	72" Bale Grapple Bolt-on Edge & Removable Grapple	84" Bale Grapple Bolt-on Edge	84" Bale Grapple Bolt-on Edge & Removable Grapple	96" Bale Grapple Bolt-on Edge	96" Bale Grapple Bolt-on Edge & Removable Grapple
	Weight	1,250 lbs	1,350 lbs	1,420 lbs	1,520 lbs	1,590 lbs	1,690 lbs


Skeleton Grapple			
	Model	KDSGT-96	
	Telehandler Mount	72" Root Grapple with a Serrated Edge	96" Root Grapple with a Serrated Edge
	Weight	1,750 lbs	1,950 lbs

Tele-Tach													
	Model	KDATT-SKY	KDATT-JLG	KDATT-JLG01	KDATT-G5519	KDATT-SJAC	KDATT-SJAC01	KDATT-Dyna13	KDATT-Dyna11	KDATT-EXTR	KDATT-BOB	KDATT-MANT	KDATT-CAT
	Telehandler Mount	Skytrak Mount	Old Style JLG	JLG 5-18A & 5-19A	Genie 5519 Mount	IR & Skyjack Mount	Sky jack S519	Wide Dyna-tach Mount	Narrow Dyna-tach Mount	Extreme Mount	Bobcat Versa-handler	Manitou Tele-handlers	Cat IT
	Weight	255 lbs	315 lbs	245 lbs	245 lbs	255 lbs	245 lbs	250 lbs	250 lbs	255 lbs	275 lbs	265 lbs	295 lbs


Square Bale Spears		
	Model	KDSBS-SQ
	Frame Width	66"
	Frame Height	36"
	Description	Four 39" Conus 2 Tines

Round Bale Spears		
	Model	KDRBS-R
	Frame Width	48"
	Frame Height	36"
	Description	One 49" Conus 2 Tines Two 24" Cold Rolled Tines


High Back Bale Spears		
	Model	KDBBS-SQH
	Frame Width	66"
	Frame Height	60"
	Description	Four 39" Conus 2 Tines

Fork Slot Truss Jib			
	Model	KDFTJ 12	KDFTJ 15
	Description	12' Fork Slot Truss Jib	15' Fork Slot Truss Jib
	Capacity	2,000 lbs	2,000 lbs
	Weight	525 lbs	575 lbs


* It comes equipped with safety chains and pins. * Available in 12' or 15' lengths.

Quick Attach Adjustable Jib			
	Model	KDAAJ-QN	KDAAJ-QW
	Description	Quick Attach Adjustable Jib	Quick Attach Adjustable Jib Wide Frame
	Capacity@ 12'	2,000 lbs	2,000 lbs
	Weight	645 lbs	851 lbs
	Description	Upgrade to two 5 ton Swivel Hooks (10,000 lbs hook)	

* IPositions ranging from 2 feet to 12 feet. * Comes standard with one 5 Ton Crosby Swivel Hook.

Telescoping Pivoting Adjustable Jib			
	Model	KDTAJ-A	KDTAJ-A-LP
	Description	Telescoping Pivoting Jib, Vertical to 35 Degree Angle (pockets 2 1/2" x 7 1/2")	Telescoping Pivoting Jib, Vertical to 35 Degree Angle (pockets 3 1/2" x 7 1/2")
	Capacity@ 12'	2,050 lbs	2,050 lbs
	Weight	645 lbs	851 lbs
	Description	Upgrade to two 5 ton Swivel Hooks (10,000 lbs hook)	


* Adjustable Jib Booms for Telehandlers * Comes standard with one 5 Ton Crosby Swivel Hook.

Quick Attach Truss Jib					
	Model	KDATJ 2	KDATJ 4	KDATJ 12	KDATJ 15
	Description	2" Quick Attach Truss Jib	4" Quick Attach Truss Jib	12' Quick Attach Truss Jib	15' Quick Attach Truss Jib
	Capacity	10,000 lbs	8,000 lbs	2,000 lbs	2,000 lbs
	Weight	/	/	575 lbs	615 lbs

Lift Capacity Rating

Jib Position	1	2	3	4	5	6	7	8	9
Length(inch)	78	86	94	102	110.25	118.5	126.75	135	143.25
Max. Lift Capacity	6,000 lbs	5,715 lbs	5,410 lbs	5,075 lbs	4,710 lbs	4,320 lbs	3,905 lbs	3,465 lbs	3,000 lbs

* Quick Attach Truss Jibs For Telehandlers. * Custom built to fit your machine. * Many lengths are available.

Industrial Jib							
	Model	KDIJ	KDIJ-3000	M001	M002	M003	M004
	Description	Industrial Jib	Industrial Jib Heavy Duty				
	Capacity@ 12'	2,050 lbs	2,900 lbs	Upgrade to one Swivel Hook for an MIJ (6,000 lbs hook)	Upgrade to two Swivel Hooks for an MIJ (6,000 lbs hook)	Upgrade to one 5 ton Swivel Hook for an MIJ-3,000 (10,000 lbs hook)	Upgrade to two 5 ton Swivel Hooks for an MIJ-3,000 (10,000 lbs hook)
	Weight	525 lbs	640 lbs				
	Remark	Upgrade and add Swivel Hooks					


* Adjustable jib booms for telehandlers. * Adjusts from 4 feet to 12 feet with 8 positions.

Model KDIJ Lift Capacity Rating

Jib Position	1	2	3	4	5	6	7	8
Length(inch)	48	66	84	96	108	120	132	144
Max. Lift Capacity	6,000 lbs	6,000 lbs	4,700 lbs	3,500 lbs	3,100 lbs	2,650 lbs	2,450 lbs	2,050 lbs

Model KDIJ-3000 Capacity Rating


Jib Position	1	2	3	4	5	6	7	8
Length(inch)	48	66	84	96	108	120	132	144
Max. Lift Capacity	10,000 lbs	8,000 lbs	6,800 lbs	5,300 lbs	4,200 lbs	3,800 lbs	3,300 lbs	2,900 lbs

Quick Attach Standard Capacity Bucket						
	Model	MDBT 60	MDBT 72	MDBT 84	MDBT 96	MDBT 102
	Description	60" High Capacity	72" High Capacity	84" High Capacity	96" High Capacity	102" High Capacity
	Bucket Height	30.0"	30.0"	30.0"	30.0"	30.0"
	Inside Depth	38.0"	38.0"	38.0"	38.0"	38.0"
	Bucket Width	60"	72"	84"	96"	102"
	Heaped Capacity	0.90 yd ³	1.10 yd ³	1.35 yd ³	1.50 yd ³	1.60 yd ³
	Weight	665 lbs	725 lbs	825 lbs	960 lbs	1,015 lbs


* Adjustable jib booms for telehandlers. * Adjusts from 4 feet to 12 feet with 8 positions.


Quick Attach High Capacity Bucket						
	Model	KDSBT 60	KDSBT 72	KDSBT 84	KDSBT 96	KDSBT 102
	Description	60" High Capacity	72" High Capacity	84" High Capacity	96" High Capacity	102" High Capacity
	Bucket Height	38.0"	38.0"	38.0"	38.0"	38.0"
	Inside Depth	42.0"	42.0"	42.0"	42.0"	42.0"
	Bucket Width	60"	72"	84"	96"	102"
	Heaped Capacity	1.55 yd ³	1.55 yd ³	1.80 yd ³	2.05 yd ³	2.15 yd ³
	Weight	785 lbs	845 lbs	1,020 lbs	1,150 lbs	1,215 lbs

* Quick Attach mounts are available for most Telehandlers.


Fork Slot Bucket										
	Model	KDFSB 60	KDFSB 66	KDFSB 72	KDFSB 96	KDFSB 108	High Capacity	KDFSB-48H-72	KDFSB-48H-96	KDSHC-01
	Bucket Height	28.0"	28.0"	28.0"	28.0"	28.0"		38.5"	38.5"	Add Shurlock Chain and Hook options (2 chains and 2 hooks per bucket)
	Inside Depth	52.0"	52.0"	52.0"	52.0"	52.0"		52.0"	52.0"	
	Bucket Width	60"	66"	72"	96"	108"		72"	96"	
	Struck Capacity	1.00 yd ³	1.10 yd ³	1.20 yd ³	1.60 yd ³	1.80 yd ³		1.6 yd ³	2.2 yd ³	
	Weight	630 lbs	695 lbs	675 lbs	850 lbs	920 lbs		750 lbs	925 lbs	


* Slips over your fork tines. * It has a high carbon 3/4" x 6" cutting edge.


Fork Slot Bucket High Capacity			
	Model	KDFSB-48H-72	KDFSB-48H-96
	Bucket Width	72"	96"
	Bucket Height	38.5"	38.5"
	Bucket Depth	52.0"	52.0"
	Struck Capacity	1.6 yd ³	2.2 yd ³
	Weight	750 lbs	925 lbs


Extended Fork Slot Bucket			
	Model	KDFSB 60D-72	KDFSB 60D-96
	Bucket Width	72"	96"
	Bucket Height	32.5"	32.5"
	Bucket Depth	64.0"	64.0"
	Struck Capacity	2.1 yd ³	2.7 yd ³
	Weight	825 lbs	1,025 lbs


* Slips on Fork Tines up to 60" long. * Standard Pocket size 3 1/2" x 7 1/2".


Adjustable Spreader Bar							
	Model	KDASPR 1320					
	Spread	Center Position - Single Point Load	Point Loads @ 65.375" spread position	Point Loads @ 110.00" spread position	Point Loads @ 162.00" spread position	Point Loads @ 201.00" spread position	Point Loads @ 240.00" spread position
	Lifting Capacity	10,000 lbs	5,000 x 2 = 10,000 lbs	4,000 x 2 = 8,000 lbs	3,500 x 2 = 7,000 lbs	3,000 x 2 = 6,000 lbs	2,250 x 2 = 4,500 lbs
	Weight	875 lbs	/	/	/	/	/


Adjustable Spreader Bar						
	Model	KDASPR 812				
	Spread	Center Position - Single Point Load	Point Loads @ 65.375" spread position	Point Loads @ 97.88" spread position	Point Loads @ 121.88" spread position	Point Loads @ 145.88" spread position
	Lifting Capacity	10,000 lbs	5,000 x 2 = 10,000 lbs	4,000 x 2 = 8,000 lbs	3,500 x 2 = 7,000 lbs	3,000 x 2 = 6,000 lbs
	Weight	580 lbs	/	/	/	/


Adjustable Spreader Bar							
	Model	KDASPR 1015					
	Spread	Center Position - Single Point Load	Point Loads @ 65.375" spread position	Point Loads @ 89.00" spread position	Point Loads @ 120.00" spread position	Point Loads @ 150.00" spread position	Point Loads @ 180.00" spread position
	Lifting Capacity	10,000 lbs	5,000 x 2 = 10,000 lbs	5,000 x 2 = 10,000 lbs	4,000 x 2 = 8,000 lbs	3,500 x 2 = 7,000 lbs	3,000 x 2 = 6,000 lbs
	Weight	685 lbs	/	/	/	/	/

Adjustable Spreader Bar with Top Hooks						
	Model	KDASPRX 812				
	Spread	Center Position - Single Point Load	Point Loads @ 65.375" spread position	Point Loads @ 97.88" spread position	Point Loads @ 121.88" spread position	Point Loads @ 145.88" spread position
	Lifting Capacity	10,000 lbs	5,000 x 2 = 10,000 lbs	4,000 x 2 = 8,000 lbs	3,500 x 2 = 7,000 lbs	3,000 x 2 = 6,000 lbs
	Weight	720 lbs	/	/	/	/

Adjustable Spreader Bar with Top Hooks							
	Model	KDASPRX 1015					
	Spread	Center Position - Single Point Load	Point Loads @ 65.375" spread position	Point Loads @ 89.00" spread position	Point Loads @ 120.00" spread position	Point Loads @ 150.00" spread position	Point Loads @ 180.00" spread position
	Lifting Capacity	10,000 lbs	5,000 x 2 = 10,000 lbs	5,000 x 2 = 10,000 lbs	4,000 x 2 = 8,000 lbs	3,500 x 2 = 7,000 lbs	3,000 x 2 = 6,000 lbs
	Weight	825 lbs	/	/	/	/	/


Adjustable Spreader Bar with Top Hooks							
	Model	KDASPRX 1320					
	Spread	Center Position - Single Point Load	Point Loads @ 63.375" spread position	Point Loads @ 110.00" spread position	Point Loads @ 162.00" spread position	Point Loads @ 201.00" spread position	Point Loads @ 240.00" spread position
	Lifting Capacity	10,000 lbs	5,000 x 2 = 10,000 lbs	4,000 x 2 = 8,000 lbs	3,500 x 2 = 7,000 lbs	3,000 x 2 = 6,000 lbs	2,250 x 2 = 4,500 lbs
	Weight	995 lbs	/	/	/	/	/

KDSPR-72 Rigid Spreader Bar							
	Model	KDSPR 72		KDSPR 96		KDSPR 144	
	Description	72" Spreader Bar		96" Spreader Bar		144" Spreader Bar	
	Capacity	10,000 lbs@ 72"	10,000 lbs @ Center Position	10,000 lbs @ 96"	10,000 lbs @ Center Position	10,000 lbs @ 144"	10,000 lbs @ Center Position
	Weight	345 lbs	/	425 lbs	/	515 lbs	/
	Optional	Optional Third Hook and Shackle - 5 ton Swivel Hook					


Swivel Hook						
	Model	KDFSH-6	KDFSH-10	KDFSH-14	KDFSH-10W	KDFSH-14W
	Capacity	6,000 lbs	10,000 lbs	14,000 lbs	10,000 lbs	14,000 lbs
	Pocket Spacing	14.5" ID. - 29.5" OD	14.5" ID. - 29.5" OD	14.5" ID. - 29.5" OD	20.5" ID. - 35.5" OD	20.5" ID. - 35.5" OD
	Weight	137 lbs	142 lbs	147 lbs	155 lbs	160 lbs
	Description	/	/	/	Wide Base	Wide Base


High Capacity Swivel Hook			
	Model	KDFSH-22	KDFSH-30
	Capacity	22,000 lbs	30,000 lbs
	Pocket Spacing	26.5" ID. - 45.5" OD	26.5" ID. - 45.5" OD
	Weight	380 lbs	395 lbs

* High Capacity Swivel Hook for Large Forklifts and Wheel Loaders.


Swivel Hook with a 2" Receiver			
	Model	KDFSH-6TS	KDFSH-10TS
	Description	3 Ton Swivel Hook with a 2" Receiver Hitch	5 Ton Swivel Hook with a 2" Receiver Hitch
	Pocket Spacing	14.5" ID. - 29.5" OD	14.5" ID. - 29.5" OD
	Weight	205 lbs	220 lbs

* Fork Mounted trailer spotter for Forklifts with a 2" receiver hitch.

Premium Swivel Hook			
	Model	KD10	KD14
	Description	10,000 lbs Swivel Hook - Frame and Hook only no load cell	14,000 lbs Swivel Hook - Frame and Hook only no load cell
	Weight	215 lbs	225 lbs
	Wide Frame	42"	42"


Swivel Hook with Smart Hook			
	Model	KD-WLS 6.5T	KD-SW-HHP
	Description	6.5 Tonne Load Shackle - This load shackle can be used with Bluetooth or a Wireless Monitor	Wireless Monitor
	Weight	12 lbs	5 lbs
	Description	14,000 lbs. capacity, Slips over your fork tines, Holds a hook at 24" on center	

Hand-held monito


	Model	SW-HHP	HHP
	Battery Type	2 x AA	1 x PP3 9v alkaline
	Battery Life	60hrs continuous	80hrs continuous
	Display Type	6 digit 25mm LCD / 6 digit 1" LCD	6 digit 25mm LCD / 6 digit 1" LCD
	Operating Temp	-10° C to +50° C / 14° F to 122° F	-10° C to +50° C / 14° F to 122° F
	Display Rate	3Hz	3Hz
	Protection	IP65 / NEMA 4X	
	Excitation	N/A	5v
	Max Sensitivity	N/A	3mv/v
	Max Resolution	1:999999 (normal mode)	
	Connectivity	Wireless 2.4GHz	6-way female binder 423 socket
	Description	Overload counter, User settable 90db audible overload alarm, 100Hz Peak hold, Pre-set tare, Wireless range 700m/2300ft	

Wireless load shackle


Model	WLS3.25T	WLS6.5T	WLS12T	WLS25T	WLS55T	WLS85T	WLS120T	WLS200T	WLS300T	WLS400T
Capacity	3.25t (7,150lb)	6.5t (14,300lb)	12t (26,400lb)	25t (55,000lb)	55t (120,000lb)	85t (185,000lb)	120t (260,000lb)	200t (440,000lb)	300t (660,000lb)	400t (880,000lb)
Resolution	0.005t (10lb)	0.005t (10lb)	0.01t (20lb)	0.02t (50lb)	0.05t (100lb)	0.05t (100lb)	0.1t (200lb)	0.2t (200lb)	0.5t (1,000lb)	0.5t (1,000lb)
Weight	2.8kg	3.2kg	8kg	18kg	25kg	45kg	85kg	254kg	374kg	614kg
Safety Factor	5:1 when used with load bobbin									
Battery Type	Load cell 4 x AA Alkaline									
Battery Life	Load cell 1,200 hours continuous									
Operating Temp	-10° C to +50° C / 14° F to 122° F									
Accuracy	± 1% of applied load									
Frequency	2.4 GHz									
System Range	700 metres / 2,300 feet									
Data Rate	3 updates per second									
Protection	IP67 / NEMA 6									
Dimension A	26.9	36.6	51.5	73	82.5	105	127	180	205	230
	1.06"	1.44"	2.03"	2.87"	3.25"	4.13"	5.00"	7.09"	8.07"	9.06"
Dimension ØB	19.1	25.4	35.1	51	57	70	82.5	125	150	175
	0.75"	1.00"	1.38"	2.01"	2.24"	2.76"	3.25"	4.92"	5.91"	6.89"
Dimension C	56.9	79.7	113	170	189.5	253	319.5	334	398	440
	2.24"	3.14"	4.45"	6.69"	7.46"	9.96"	12.58"	13.15"	15.67"	17.32"
Dimension D	16	22.4	31.8	44.5	51	66.5	76	120	130	165
	0.63"	0.88"	1.25"	1.75"	2.01"	2.62"	2.99"	4.72"	5.12"	6.50"
Dimension E	42.9	58	82.5	127	164	184	200	290	305	325
	1.69"	2.28"	3.25"	5.00"	6.46"	7.24"	7.87"	11.42"	12.01"	12.80"
Dimension H	106	148	210	313	348	453	546	810	950	1100
	4.17"	5.83"	8.27"	12.32"	13.70"	17.83"	21.50"	31.89"	37.40"	43.31"
Dimension L	127.1	156.5	196	281	306	368	408	580	615	705
	5.00"	6.16"	7.72"	11.06"	12.05"	14.49"	16.06"	22.83"	24.21"	27.76"
Dimension N	17.5	24.6	35.1	57	61	79	92	120	130	165
	0.69"	0.97"	1.38"	2.24"	2.40"	3.11"	3.62"	4.72"	5.12"	6.50"
Dimension P	143	173	218	293	317	394	441	565	615	711
	5.63"	6.81"	8.58"	11.54"	12.48"	15.51"	17.36"	22.24"	24.21"	27.99"
Description	Proprietary 2.4 GHz wireless, Error free data transmission, Industry Leading Wireless Range of 700m/2300ft, Environmentally sealed to IP67/NEMA6, Internal antennae, Remote on/off, Unrivaled resolution, Unmatched battery life of 1200hrs, Low headroom solution.									




Work Platform

	Model	KDWP 4x4	KDWP 4x6	KDWP 4x8	KDWP 4x116
	Size	4'x4'	4'x6'	4'x8'	4'x9'8"
	Doors	1 Door	1 Door	2 Doors	2 Doors
	Capacity	1,000 lbs	1,000 lbs	1,000 lbs	1,000 lbs
	Weight	395 lbs	487 lbs	578 lbs	630 lbs
	Description	Safety pins are standard for all side rails. Each pin is attached to the rail by a cable to prevent losing the safety pins, Spring Loaded Doors gives the door extra strength and allows the door to remain rigid at all times, Safety Restraint Tie Down are standard on all platforms.			

Galvanized Work Platform

	Model	KDGWP 4x4	KDGWP 4x6	KDGWP 4x8	KDGWP 4x116
	Size	4x4	4x6	4x8	4x9'8"
	Capacity	1,000 lbs	1,000 lbs	1,000 lbs	1,000 lbs
	Weight	415 lbs	522 lbs	618 lbs	675 lbs
	Description	Safety pins are standard for all side rails. Each pin is attached to the rail by a cable to prevent losing the safety pins, Spring Loaded Doors gives the door extra strength and allows the door to remain rigid at all times, Safety Restraint Tie Down are standard on all platforms.			

Handyman Platforms

	Model	KDHP 4x4	KDHP 4x6
	Doors	1 Door	1 Door
	Capacity	1,000 lbs	1,000 lbs
	Weight	410 lbs	507 lbs
	Standard pocket size	ID 2.75" x 7.75". Spacing between pockets is 30"	
	Description	4x4 Platform with Highback for Mast Style forklifts.	4x4 Platform with Highback for Mast Style forklifts.

* Heavy duty steel mesh floor for for years of dependability. * 60" Tall High back.